



Power LED:
 電源供給中点灯(緑)
 /Lighting while supplied power
 Alarm LED:
 炎検知時点灯(赤)、復帰時消灯
 /Lighting while detected fire

7	Alarm LED	RED LED	1	φ5.2mm
6	Power LED	Green LED	1	φ5.2mm
5	Cable	PVC	1	H-VCT-F 0.2mm2 x 4c
4	Nut	PP	1	Gray
3	Window glass	sapphire	1	—
2	Case2	PP	1	Smoke White
1	Case1	PP	1	Smoke White

No.	Parts Name (部品名)	Material (材質)	Q'TY	Remarks (備考)	
	Date (日付)	Scale (尺度)	DSGN'D (設計)	CHK'D (検閲)	APRV'D (承認)

	2010.01.14	NONE	渥美	小坂井	小坂井
HATSUTA SEISAKUSHO CO.,LTD.		Drawing No. (図番)			
(株) 初田製作所		CXR-29601-5			

Total Weight: Approx. 990g (Body is Approx 160g)
 Cable overall diameter (外径): Approx 5.5mm
 Cable sheath material (外皮材質): 105°C heat resistant PVC
 (105°C耐熱ビニル)

RoHS対応品

FM Approved

Flame Detector SX-7000
 Model(型式): HIR-7000-20